

# Technical data sheet

## 6035 Headset

Art. no 14774 and 17147



### DESCRIPTION:

6035 is a hearing protective headset for use together with Intercom Systems in noisy environments. The headset is equipped with high attenuating shells with optimised acoustic design and excellent space for the ears for the best possible sound quality and comfort. The headset microphone is a quick positioning noise cancelling boom microphone. The headset is equipped with an ON/OFF hook switch.

### FEATURES:

- Excellent noise performance microphone
- High attenuating ear shells
- 10m or 15m cable
- Hook switch



### ELECTRICAL SPECIFICATIONS:

Termination	Flying leads
Microphone	Dynamic, Noise Cancelling (12dB), 230Ω, 4mV, 70-9000Hz
Earphone	50Ω, 81dBA at 0.5V/1kHz
Compass safe distance	>5m

### ENVIRONMENTAL SPECIFICATIONS:

Temperature	-15°C to +55°C
Humidity	+93% (at +40°C)
Protection	IP 54 (when in use)
Attenuation rating (HML)	H=33dB / M=32dB / L=24dB
Attenuation rating (SNR)	33 dB

# Technical data sheet

## 6035 Headset

Art. no 14774 and 17147



### MECHANICAL SPECIFICATIONS:

Dimension (HxD)	Approximately 200x95mm
Weight	0.7kg
Colour	RAL 9006
Cable	14774: 10m flexible durable cable 17147: 15m flexible durable cable
Manufacturer	Jotron AS (3M™ Peltor MT7H79A-65)

### CERTIFICATES / COMPLIANCES:

Complies to IEC 60945 Marine equipment
The unit has a DNV-GL, ABS, CCS and RMRS type approval
PPE directive 89/686/EEC
Applicable parts of EN352-1:1993

### PRODUCT RELATED TO:

ICS 6200	Integrated Communication System
6112	Unit without handset, weather protected
5111-H	Telephone, watertight
11220	Bracket for headset

# Technical data sheet

## 6035 Headset

Art. no 14774 and 17147



### DIMENSION / LAYOUT

