

KEY FEATURES

Signalling

- Private Line™
- 5-tone selective signalling

Easy to use and set-up

- Programmable buttons for easy access to frequently used features
- Ruggedised design

Protecting users

- Emergency signalling
- Lone worker feature for staff working remotely
- Whisper mode for discreet communications

Quality

- MIL Spec 810 compliant
- Meets IP54 environmental standards
- Passed Motorola Accelerated Life Test
- X-Pand™ voice compression technology

Efficiency

- Channel scanning
- Call management features include call forwarding and escalating incoming call alert

Included as standard

- Battery
- Antenna
- Belt clip
- Accessory dust cover
- User manual

Accessory options

A wide range of accessory options are available to customise your radio

- Audio accessories
- Batteries and chargers
- Carry options

For full details of available accessories, please contact your local dealer or distributor



GP340

Communication Made Easy.

The GP340, one of the market-leading radios in Motorola's Professional Series, is a simple communication solution for portable users requiring a high-quality radio. The GP340 keeps users in touch; increasing efficiency and productivity. The radio offers essential functionality and security features to protect users working alone or remotely.

With option board capability and a wide range of accessories available within the Professional Series; it's easy to build a tailored communications solution to meet your needs.

SPECIFICATIONS

GENERAL SPECIFICATIONS

Channel Capacity	16
Power Supply	Rechargeable Battery 7.5v
Dimensions: H x W x D (mm)	Height excluding knobs
With Standard high capacity NiMH battery	137 x 57.5 x 37.5
With ultra high capacity NiMH battery	137 x 57.5 x 40.0
With NiCD battery	137 57.5 x 40.0
With Li-Ion battery	137 x 57.5 x 33.0
Weight: (gm)	
With Standard high capacity NiMH battery	420
With Ultra high capacity NiMH battery	500
With NiCD battery	450
With Li-Ion battery	350
Average battery Life @5/5/90 Cycle:	Low Power High Power
With Standard high capacity NiMH battery	11 hours 8 hours
With Ultra high capacity NiMH battery	14 hours 11 hours
With NiCD battery	12 hours 9 hours
With Li-Ion	11 hours 8 hours

GENERAL SPECIFICATIONS (continued)

Sealing:	Withstands rain testing per MIL STD 810 C/D/E and IP54
Shock and Vibration:	Protection provided via impact resistant housing exceeding MIL STD 810-C/D/E and TIA/EIA 603
Dust and Humidity:	Protection provided via environment resistant housing exceeding MIL STD 810 C/D/E and TIA/EIA 603
Operating temperature:	-20°C to +55°C

Data is specified for +25°C unless otherwise stated.

PORTABLE MILITARY STANDARDS 810 C, D & E

Applicable MIL-STD	810C		810D		810E	
	Methods	Procedures	Methods	Procedures	Methods	Procedures
Low Pressure	500.1	1	500.2	2	500.3	2
High Temperature	500.1	1,2	501.2	1,2	501.3	1,2
Low Temperature	502.1	1	502.2	1,2	502.3	1,2
Temp. Shock	503.1	1	503.2	1	503.3	1
Solar Radiation	505.1	1	505.2	1	505.3	1
Rain	506.1	1,2	506.2	1,2	506.3	1,2
Humidity	507.1	2	507.2	2,3	507.3	2,3
Salt Fog	509.1	1	509.2	1	509.3	1
Dust	510.1	1	510.2	1	510.3	1
Vibration	514.2	8,10	514.3	1	514.4	1
Shock	516.2	1,2,5	516.3	1,4	516.4	1,4

TRANSMITTER

*Frequencies - Full Bandsplit	VHF: 136-174 MHz UHF: 300-350 MHz UHF1: 403-470 MHz	LB1: 29.7-42 MHz LB2: 35-50 MHz
Channel Spacing	12.5/20/25 kHz	12.5/20/25 kHz
Frequency Stability (-25°C to +55°C, + 25°C Ref.)	±2.5 ppm	±10ppm
Power	136-174: 1-5W 300-350: 1-4W 403-470: 1-4W	1-6W
Modulation Limiting	±2.5 @ 12.5 kHz ±4.0 @ 20 kHz ±5.0 @ 25 kHz	±2.5 @ 12.5kHz ±4.0 @ 20 kHz ±5.0 @ 25 kHz
FM Hum & Noise	-40dB typical	-40dB typical
Conducted/Radiated Emission	-36 dBm <1 GHz -30 dBm >1GHz	-36 dBm 1000MHz -30 dBm 1000MHz
Adjacent Channel Power	-60 dB @ 12.5 kHz -70 dB @ 20/25 kHz	-60 dB @ 12.5 kHz -70 dB @ 25 kHz
Audio Response (300-3000Hz)	+1 to -3 dB	+1 to -3 dB
Audio Distortion	3%	3%

RECEIVER

*Frequencies - Full Bandsplit	VHF: 136-174 MHz UHF: 300-350 MHz UHF1: 403-470 MHz	LB1: 29.7-42 MHz LB2: 35-50 MHz
Channel Spacing	12.5/20/25 kHz	12.5/20/25 kHz
Sensitivity (12 dB SINAD) EIA	.25µV typical	.25µV typical
Sensitivity (20 dB SINAD) EN	.50µV typical	.50µV typical
Intermodulation EIA	70 dB	70 dB
Adjacent Channel Selectivity	60 dB @ 12.5 kHz 70 dB @ 20/25 kHz	60 dB @ 12.5 kHz 70 dB @ 25 kHz
Spurious Rejection	70 dB	70 dB
Rated Audio	0.5W	0.5W
Audio Distortion @ Rated Audio	3% typical	3% typical
Hum & Noise	-40 dB @ 12.5 kHz -50 @ 20/25 kHz	-45 @ 12.5 kHz -50 @ 20/25 kHz
Audio Response (300-3000 Hz)	+1 to -3 dB	+1 to -3dB
Conducted Spurious Emission	-57 dBm <1 GHz -47 dBm <1 GHz EN 300 086	-57 dBm <1 GHz -47 dBm <1 GHz FCC Part 15

*Availability subject to individual country's law and regulations.

Specifications are subject to change without notice and are issued for guidance only.

All specifications listed are typical. Radios meet applicable regulatory requirements.

Conforms to EC directive 89/336/EEC

Complies with EN 300 113

Contact your local Motorola Authorised Dealer to find out more about how communicating with the Professional Radio series will benefit your organisation.



Motorola Limited, EMEA Headquarters

Jays Close, Viabes Industrial Estate, Basingstoke, RG22 4PD, UK
Telephone: +44 (0)1256 358211

www.motorola.com

MOTOROLA and the Stylised M Logo are registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners.
© Motorola, Inc. 2006. All rights reserved.

GP340-RE(08/06)